Indiana Department of Environmental Management



? make Indiana a cleaner, healthier place to live.

Joseph E. Kernan Governor

Lori F. Kaplan
Commissioner

6015

100 North Senate AvenueP. O. Box 6015Indianapolis, Indiana 46206-

(317) 232-8603 (800) 451-6027 www.state.in.us/idem

FEDERALLY ENFORCEABLE STATE OPERATING PERMIT (FESOP) OFFICE OF AIR QUALITY

Total Interior Systems - America, LLC Rural Route 1, Box 101 County Road 100 Princeton, Indiana 47670

(herein known as the Permittee) is hereby authorized to operate subject to the conditions contained herein, the source described in Section A (Source Summary) of this permit.

The Permittee must comply with all conditions of this permit. Noncompliance with any provisions of this permit is grounds for enforcement action; permit termination, revocation and reissuance, or modification; or denial of a permit renewal application. Noncompliance with any provision of this permit, except any provision specifically designated as not federally enforceable, constitutes a violation of the Clean Air Act. It shall not be a defense for the Permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of this permit. An emergency does constitute an affirmative defense in an enforcement action provided the Permittee complies with the applicable requirements set forth in Section B, Emergency Provisions.

This permit is issued in accordance with 326 IAC 2 and 40 CFR Part 70 Appendix A and contains the conditions and provisions specified in 326 IAC 2-8 as required by 42 U.S.C. 7401, et. seq. (Clean Air Act as amended by the 1990 Clean Air Act Amendments), 40 CFR Part 70.6, IC 13-15 and IC 13-17.

Operation Permit No.: F051-17729-00045		
Issued by: Original signed by	Issuance Date: January 8, 2004	
Paul Dubenetzky, Branch Chief Office of Air Quality	Expiration Date: January 8, 2009	

Total Interior Systems - America, LLC

Princeton, Indiana

Permit Reviewer: ERG/SD

C.11

C.12

Page 2 of 35 F051-17729-00045

TABLE OF CONTENTS

SECTION A	SOURCE SUMMARY
A.1	General Information [326 IAC 2-8-3(b)]
A.2	Emission Units and Pollution Control Equipment Summary [326 IAC 2-8-3(c)(3)]
A.3	Insignificant Activities [326 IAC 2-7-1(21)] [326 IAC 2-8-3(c)(3)(I)]
A.4	FESOP Applicability [326 IAC 2-8-2]
A.5	Prior Permits Superseded [326 IAC 2-1.1-9.5]
SECTION B	GENERAL CONDITIONS
B.1	Permit No Defense [IC 13]
B.2	Definitions [326 IAC 2-8-1]
B.3	Permit Term [326 IAC 2-8-4(2)] [326 IAC 2-1.1-9.5]
B.4	Enforceability [326 IAC 2-8-6]
B.5	Termination of Right to Operate [326 IAC 2-8-9][326 IAC 2-8-3(h)]
B.6	Severability [326 IAC 2-8-4(4)]
B.7	Property Rights or Exclusive Privilege [326 IAC 2-8-4(5)(D)]
B.8	Duty to Provide Information [326 IAC 2-8-4(5)(E)]
B.9	Compliance Order Issuance [326 IAC 2-8-5(b)]
B.10	Certification [326 IAC 2-8-3(d)] [326 IAC 2-8-4(3)(C)(i)] [326 IAC 2-8-5(1)]
B.11	Annual Compliance Certification [326 IAC 2-8-5(a)(1)]
B.12	Preventive Maintenance Plan [326 IAC 1-6-3][326 IAC 2-8-4(9)][326 IAC 2-8-5(a)(1)]
B.13	Emergency Provisions [326 IAC 2-8-12]
B.14	Deviations from Permit Requirements and Conditions [326 IAC 2-8-4(3)(C)(ii)]
B.15	Permit Modification, Reopening, Revocation and Reissuance, or Termination [326 IAC 2-8-
	4(5)(C)] [326 IAC 2-8-7(a)] [326 IAC 2-8-8]
B.16	Permit Renewal [326 IAC 2-8-3(h)]
B.17	Permit Amendment or Revision [326 IAC 2-8-10][326 IAC 2-8-11.1]
B.18	Operational Flexibility [326 IAC 2-8-15] [326 IAC 2-8-11.1]
B.19	Permit Revision Requirement [326 IAC 2-8-11.1]
B.20	Inspection and Entry [326 IAC 2-8-5(a)(2)] [IC 13-14-2-2] [IC 13-30-3-1]
B.21	Transfer of Ownership or Operational Control [326 IAC 2-8-10]
B.22	Annual Fee Payment [326 IAC 2-7-19] [326 IAC 2-8-4(6)] [326 IAC 2-8-16]
	[326 IAC 2-1.1-7]
SECTION C	SOURCE OPERATION CONDITIONS
Emiss	ion Limitations and Standards [326 IAC 2-8-4(1)]
C.1	Particulate Emission Limitations For Processes with Process Weight Rates Less Than
	One Hundred (100) pounds per hour [40 CFR 52 Subpart P][326 IAC 6-3-2]
C.2	Overall Source Limit [326 IAC 2-8]
C.3	Opacity [326 IAC 5-1]
C.4	Open Burning [326 IAC 4-1][IC 13-17-9]
C.5	Incineration [326 IAC 4-2] [326 IAC 9-1-2(3)]
C.6	Fugitive Dust Emissions [326 IAC 6-4]
C.7	Operation of Equipment [326 IAC 2-8-5(a)(4)]
C.8	Asbestos Abatement Projects [326 IAC 14-10] [326 IAC 18] [40 CFR 61, Subpart M]
	g Requirements [326 IAC 2-8-4(3)]
C.9	Performance Testing [326 IAC 3-6]
-	liance Requirements [326 IAC 2-1.1-11]
C.10	Compliance Requirements [326 IAC 2-1.1-11]
Comp	liance Monitoring Requirements [326 IAC 2-8-4] [326 IAC 2-8-5(a)(1)]

Compliance Monitoring [326 IAC 2-8-4(3)] [326 IAC 2-8-5(a)(1)]

Monitoring Methods [326 IAC 3][40 CFR 60][40 CFR 63]

Total Interior Systems - America, LLC Princeton, Indiana

Permit Reviewer: ERG/SD

TABLE OF CONTENTS (Continued)

Page 3 of 35 F051-17729-00045

Correct	ive Acti	ons and Response Steps [326 IAC 2-8-4] [326 IAC 2-8-5]
	C.13	Risk Management Plan [326 IAC 2-8-4] [40 CFR 68]
	C.14	Compliance Response Plan - Preparation, Implementation, Records, and Reports [326 IAC 2-8-4] [326 IAC 2-8-5]
	C.15	Actions Related to Noncompliance Demonstrated by a Stack Test [326 IAC 2-8-4] [326 IAC 2-8-5]
	Record C.16 C.17	Keeping and Reporting Requirements [326 IAC 2-8-4(3)] General Record Keeping Requirements [326 IAC 2-8-4(3)][326 IAC 2-8-5] General Reporting Requirements [326 IAC 2-8-4(3)(C)] [326 IAC 2-1.1-11]
	Stratos	spheric Ozone Protection
	C.18	Compliance with 40 CFR 82 and 326 IAC 22-1
SECTIO	N D.1	FACILITY OPERATION CONDITIONS
	Emissi	on Limitations and Standards [326 IAC 2-8-4(1)]
	D.1.1	Hazardous Air Pollutants and Volatile Organic Compounds [326 IAC 2-8-4]
	D.1.2	Volatile Organic Compounds (VOCs) [326 IAC 8-1-6]
	D.1.3	Particulate Matter (PM) [40 CFR Subpart P]
	D.1.4	·
	D.1.5	Preventive Maintenance Plan [326 IAC 2-8-4(9)]
	Compli	iance Determination Requirements
	D.1.6	HAP and VOC Emissions
	Compli D.1.7	ance Monitoring Requirements [326 IAC 2-8-4] [326 IAC 2-8-5(a)(1)] Monitoring
	Record	Keeping Requirements [326 IAC 2-8-4(3)] [326 IAC 2-8-16]
	D.1.8	Record Keeping Requirements
	D.1.9	Reporting Requirements
SECTIO	N D.2	FACILITY OPERATION CONDITIONS
	Emissi	on Limitations and Standards
		m
		currence Form
		ly Reports
Quarterl	y Deviat	tion and Compliance Monitoring Report Form

Total Interior Systems - America, LLC Page 4 of 35
Princeton, Indiana F051-17729-00045

Permit Reviewer: ERG/SD

SECTION A SOURCE SUMMARY

This permit is based on information requested by the Indiana Department of Environmental Management (IDEM), Office of Air Quality (OAQ). The information describing the source contained in conditions A.1, A.2, and A.3 is descriptive information and does not constitute enforceable conditions. However, the Permittee should be aware that a physical change or a change in the method of operation that may render this descriptive information obsolete or inaccurate may trigger requirements for the Permittee to obtain additional permits or seek modification of this permit pursuant to 326 IAC 2, or change other applicable requirements presented in the permit application.

A.1 General Information [326 IAC 2-8-3(b)]

The Permittee owns and operates a stationary vehicle door panel manufacturing plant.

Authorized Individual: General Manager

Source Address: Rural Route 1, Box 101 County Road 100, Princeton, Indiana 47670 Mailing Address: Rural Route 1, Box 101 County Road 100, Princeton, Indiana 47670

General Source Phone: (812) 491-9101

SIC Code: 2396 County: Gibson

Source Location Status: Attainment for all other criteria pollutants

Source Status: Federally Enforceable State Operating Permit (FESOP)

Minor Source, under PSD Rules;

Minor Source, Section 112 of the Clean Air Act

Not in 1 of 28 Source Categories

A.2 Emission Units and Pollution Control Equipment Summary [326 IAC 2-8-3(c)(3)]

This stationary source consists of the following emission units and pollution control devices:

- (a) Three (3) spray booths (identified as EU 02, 03 and 04), using three (3) HVLP guns, each with a maximum throughput rate of 8.64 gallons of coating per hour, using dry filters for over spray control and exhausting to stacks ID 02, 03 and 04.
- (b) One (1) red spot spray booth (identified as EU 01), using one (1) HVLP gun, with a maximum throughput rate of 0.41 gallons of coating per hour, using dry filters for over spray control and exhausting to stack ID 01.

A.3 Insignificant Activities [326 IAC 2-7-1(21)] [326 IAC 2-8-3(c)(3)(I)]

This stationary source also includes the following insignificant activity, as defined in 326 IAC 2-7-1(21).

(a) One (1) 1,000 kW diesel emergency generator burning No. 2 fuel oil.

A.4 FESOP Applicability [326 IAC 2-8-2]

This stationary source, otherwise required to have a Part 70 permit as described in 326 IAC 2-7-2(a), has applied to the Indiana Department of Environmental Management (IDEM), Office of Air Quality (OAQ) for a Federally Enforceable State Operating Permit (FESOP).

A.5 Prior Permits Superseded [326 IAC 2-1.1-9.5]

- (a) All terms and conditions of previous permits issued pursuant to permitting programs approved into the state implementation plan have been either
 - (1) incorporated as originally stated,
 - (2) revised, or
 - (3) deleted

Total Interior Systems - America, LLC Princeton, Indiana

Permit Reviewer: ERG/SD

by this permit.

(b) All previous registrations and permits are superseded by this permit.

Page 5 of 35 F051-17729-00045 Total Interior Systems - America, LLC Page 6 of 35
Princeton, Indiana F051-17729-00045

Permit Reviewer: ERG/SD

SECTION B GENERAL CONDITIONS

B.1 Permit No Defense [IC 13]

Indiana statutes from IC 13 and rules from 326 IAC, quoted in conditions in this permit, are those applicable at the time the permit was issued. The issuance or possession of this permit shall not alone constitute a defense against an alleged violation of any law, regulation or standard, except for the requirement to obtain a FESOP under 326 IAC 2-8.

B.2 Definitions [326 IAC 2-8-1]

Terms in this permit shall have the definition assigned to such terms in the referenced regulation. In the absence of definitions in the referenced regulation, the applicable definitions found in the statutes or regulations (IC 13-11, 326 IAC 1-2, and 326 IAC 2-7) shall prevail.

B.3 Permit Term [326 IAC 2-8-4(2)] [326 IAC 2-1.1-9.5]

This permit is issued for a fixed term of five (5) years from the original date of this permit, as determined in accordance with IC 4-21.5-3-5(f) and IC 13-15-5-3. Subsequent revisions, modifications, or amendments of this permit do not affect the expiration date.

B.4 Enforceability [326 IAC 2-8-6]

Unless otherwise stated, all terms and conditions in this permit, including any provisions designed to limit the source's potential to emit, are enforceable by IDEM, the United States Environmental Protection Agency (U.S. EPA) and by citizens in accordance with the Clean Air Act.

B.5 Termination of Right to Operate [326 IAC 2-8-9] [326 IAC 2-8-3(h)]

The Permittee's right to operate this source terminates with the expiration of this permit unless a timely and complete renewal application is submitted at least nine (9) months prior to the date of expiration of the source's existing permit, consistent with 326 IAC 2-8-3(h) and 326 IAC 2-8-9.

B.6 Severability [326 IAC 2-8-4(4)]

The provisions of this permit are severable; a determination that any portion of this permit is invalid shall not affect the validity of the remainder of the permit.

B.7 Property Rights or Exclusive Privilege [326 IAC 2-8-4(5)(D)]

This permit does not convey any property rights of any sort, or any exclusive privilege.

B.8 Duty to Provide Information [326 IAC 2-8-3(f)] [326 IAC 2-8-4(5)(E)] [326 IAC 2-8-5(a)(4)]

- (a) The Permittee shall furnish to IDEM, OAQ, within a reasonable time, any information that IDEM, OAQ, may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating this permit, or to determine compliance with this permit. The submittal by the Permittee does require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1). Upon request, the Permittee shall also furnish to IDEM, OAQ, copies of records required to be kept by this permit.
- (b) For information furnished by the Permittee to IDEM, the Permittee may include a claim of confidentiality in accordance with 326 IAC 17.1. When furnishing copies of requested records directly to U. S. EPA, the Permittee may assert a claim of confidentiality in accordance with 40 CFR 2, Subpart B.

B.9 Compliance Order Issuance [326 IAC 2-8-5(b)]

IDEM, OAQ may issue a compliance order to this Permittee upon discovery that this permit is in nonconformance with an applicable requirement. The order may require immediate compliance or contain a schedule for expeditious compliance with the applicable requirement.

B.10 Certification [326 IAC 2-8-3(d)] [326 IAC 2-8-4(3)(C)(i)] [326 IAC 2-8-5(1)]

Total Interior Systems - America, LLC Page 7 of 35
Princeton, Indiana F051-17729-00045

Permit Reviewer: ERG/SD

(a) Where specifically designated by this permit or required by an applicable requirement, any application form, report, or compliance certification submitted shall contain certification by an authorized individual of truth, accuracy, and completeness. This certification, shall state that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete.

- (b) One (1) certification shall be included, using the attached Certification Form, with each submittal requiring certification.
- (c) An authorized individual is defined at 326 IAC 2-1.1-1(1).

B.11 Annual Compliance Certification [326 IAC 2-8-5(a)(1)]

(a) The Permittee shall annually submit a compliance certification report which addresses the status of the source's compliance with the terms and conditions contained in this permit, including emission limitations, standards, or work practices. The initial certification shall cover the time period from the date of final permit issuance through December 31 of the same year. All subsequent certification shall cover the time period from January 1 to December 31 of the previous year, and shall be submitted in letter form no later than July 1 of each year to:

Indiana Department of Environmental Management Compliance Branch, Office of Air Quality 100 North Senate Avenue, P.O. Box 6015 Indianapolis, Indiana 46206-6015

- (b) The annual compliance certification report required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ, on or before the date it is due.
- (c) The annual compliance certification report shall include the following:
 - (1) The appropriate identification of each term or condition of this permit that is the basis of the certification;
 - (2) The compliance status;
 - (3) Whether compliance was continuous or intermittent;
 - (4) The methods used for determining the compliance status of the source, currently and over the reporting period consistent with 326 IAC 2-8-4(3); and
 - (5) Such other facts as specified in Sections D of this permit, IDEM, OAQ, may require to determine the compliance status of the source.

The notification which shall be submitted by the Permittee does require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).

B.12 Preventive Maintenance Plan [326 IAC 1-6-3] [326 IAC 2-8-4(9)] [326 IAC 2-8-5(a)(1)]

- (a) If required by specific condition(s) in Section D of this permit, the Permittee shall-prepare and maintain Preventive Maintenance Plans (PMPs), within ninety (90) days after issuance of this permit, including the following information on each facility:
 - (1) Identification of the individual(s) responsible for inspecting, maintaining, and repairing emission control devices;

Total Interior Systems - America, LLC Page 8 of 35
Princeton, Indiana F051-17729-00045

Permit Reviewer: ERG/SD

(2) A description of the items or conditions that will be inspected and the inspection schedule for said items or conditions; and

(3) Identification and quantification of the replacement parts that will be maintained in inventory for quick replacement.

If due to circumstances beyond the Permittee's control, the PMPs cannot be prepared and maintained within the above time frame, the Permittee may extend the date an additional ninety (90) days provided the Permittee notifies:

Indiana Department of Environmental Management Compliance Branch, Office of Air Quality 100 North Senate Avenue, P. O. Box 6015 Indianapolis, Indiana 46206-6015

The PMP extension notification does not require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).

- (b) The Permittee shall implement the PMPs, including any required recordkeeping, as necessary to ensure that failure to implement a PMP does not cause or contribute to an exceedance of any limitation on emissions or potential to emit.
- (c) A copy of the PMPs shall be submitted to IDEM, OAQ, upon request and within a reasonable time, and shall be subject to review and approval by IDEM, OAQ. IDEM, OAQ, may require the Permittee to revise its PMPs whenever lack of proper maintenance causes or is the primary contributor to an exceedance of any limitation on emissions or potential to emit. The PMP does not require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).
- (d) To the extent the Permittee is required by 40 CFR Part 60/63 to have an Operation, Maintenance, and Monitoring (OMM) Plan for a unit, such Plan is deemed to satisfy the PMP requirements of 326 IAC 1-6-3 for that unit.

B.13 Emergency Provisions [326 IAC 2-8-12]

- (a) An emergency, as defined in 326 IAC 2-7-1(12), is not an affirmative defense for an action brought for noncompliance with a federal or state health-based emission limitation, except as provided in 326 IAC 2-8-12.
- (b) An emergency, as defined in 326 IAC 2-7-1(12), constitutes an affirmative defense to an action brought for noncompliance with a health-based or technology-based emission limitation if the affirmative defense of an emergency is demonstrated through properly signed, contemporaneous operating logs or other relevant evidence that describes the following:
 - (1) An emergency occurred and the Permittee can, to the extent possible, identify the causes of the emergency;
 - (2) The permitted facility was at the time being properly operated;
 - (3) During the period of an emergency, the Permittee took all reasonable steps to minimize levels of emissions that exceeded the emission standards or other requirements in this permit;
 - (4) For each emergency lasting one (1) hour or more, the Permittee notified IDEM, OAQ, and Southwest Regional Office, within four (4) daytime business hours after the beginning of the emergency, or after the emergency was discovered or reasonably should have been discovered;

Total Interior Systems - America, LLC Page 9 of 35
Princeton, Indiana F051-17729-00045

Permit Reviewer: ERG/SD

IDEM, OAQ

Telephone No.: 1-800-451-6027 (ask for Office of Air Quality, Compliance Section)

or,

Telephone No.: 317-233-5674 (ask for Compliance Section)

Facsimile No.: 317-233-5967

Southwest Regional Office

Telephone No.: 1-888-672-8323 or (812) 380-2305

Facsimile No.: (812) 380-2307

(5) For each emergency lasting one (1) hour or more, the Permittee submitted the attached Emergency Occurrence Report Form or its equivalent, either by mail or facsimile to:

Indiana Department of Environmental Management Compliance Branch, Office of Air Quality 100 North Senate Avenue, P.O. Box 6015 Indianapolis, Indiana 46206-6015

within two (2) working days of the time when emission limitations were exceeded due to the emergency.

The notice fulfills the requirement of 326 IAC 2-8-4(3)(C)(ii) and must contain the following:

- (A) A description of the emergency;
- (B) Any steps taken to mitigate the emissions; and
- (C) Corrective actions taken.

The notification which shall be submitted by the Permittee does not require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).

- (6) The Permittee immediately took all reasonable steps to correct the emergency.
- (c) In any enforcement proceeding, the Permittee seeking to establish the occurrence of an emergency has the burden of proof.
- (d) This emergency provision supersedes 326 IAC 1-6 (Malfunctions). This permit condition is in addition to any emergency or upset provision contained in any applicable requirement.
- (e) IDEM, OAQ, may require that the Preventive Maintenance Plans required under 326 IAC 2-8-3(c)(6) be revised in response to an emergency.
- (f) Failure to notify IDEM, OAQ, by telephone or facsimile of an emergency lasting more than one (1) hour in accordance with (b)(4) and (5) of this condition shall constitute a violation of 326 IAC 2-8 and any other applicable rules.
- (g) Operations may continue during an emergency only if the following conditions are met:
 - (1) If the emergency situation causes a deviation from a technology-based limit, the Permittee may continue to operate the affected emitting facilities during the emergency provided the Permittee immediately takes all reasonable steps to correct the emergency and minimize emissions.

Total Interior Systems - America, LLC Page 10 of 35
Princeton, Indiana F051-17729-00045

Permit Reviewer: ERG/SD

(2) If an emergency situation causes a deviation from a health-based limit, the Permittee may not continue to operate the affected emissions facilities unless:

- (A) The Permittee immediately takes all reasonable steps to correct the emergency situation and to minimize emissions; and
- (B) Continued operation of the facilities is necessary to prevent imminent injury to persons, severe damage to equipment, substantial loss of capital investment, or loss of product or raw material of substantial economic value.

Any operations shall continue no longer than the minimum time required to prevent the situations identified in (g)(2)(B) of this condition.

(h) The Permittee shall include all emergencies in the Quarterly Deviation and Compliance Monitoring Report.

B.14 Deviations from Permit Requirements and Conditions [326 IAC 2-8-4(3)(C)(ii)]

(a) Deviations from any permit requirements (for emergencies see Section B - Emergency Provision), the probable cause of such deviations, and any response steps or preventive measures taken shall be reported to:

Indiana Department of Environmental Management Compliance Data Section, Office of Air Quality 100 North Senate Avenue, P.O. Box 6015 Indianapolis, Indiana 46206-6015

using the attached Quarterly Deviation and Compliance Monitoring Report, or its equivalent. A deviation required to be reported pursuant to an applicable requirement that exists independently of this permit, shall be reported according to the schedule stated in the applicable requirement and does not need to be included in this report.

The Quarterly Deviation and Compliance Monitoring Report does require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).

(b) A deviation is an exceedance of a permit limitation or a failure to comply with a requirement of the permit.

B.15 Permit Modification, Reopening, Revocation and Reissuance, or Termination [326 IAC 2-8-4(5)(C)] [326 IAC 2-8-7(a)] [326 IAC 2-8-8]

- (a) This permit may be modified, reopened, revoked and reissued, or terminated for cause. The filing of a request by the Permittee for a FESOP modification, revocation and reissuance, or termination, or of a notification of planned changes or anticipated noncompliance does not stay any condition of this permit. [326 IAC 2-8-4(5)(C)] The notification by the Permittee does require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).
- (b) This permit shall be reopened and revised under any of the circumstances listed in IC 13-15-7-2 or if IDEM, OAQ determines any of the following:
 - (1) That this permit contains a material mistake.
 - (2) That inaccurate statements were made in establishing the emissions standards or other terms or conditions.
 - (3) That this permit must be revised or revoked to assure compliance with an applicable requirement. [326 IAC 2-8-8(a)]

Total Interior Systems - America, LLC Page 11 of 35
Princeton, Indiana F051-17729-00045

Permit Reviewer: ERG/SD

(c) Proceedings by IDEM, OAQ, to reopen and revise this permit shall follow the same procedures as apply to initial permit issuance and shall affect only those parts of this permit for which cause to reopen exists. Such reopening and revision shall be made as expeditiously as practicable. [326 IAC 2-8-8(b)]

(d) The reopening and revision of this permit, under 326 IAC 2-8-8(a), shall not be initiated before notice of such intent is provided to the Permittee by IDEM, OAQ, at least thirty (30) days in advance of the date this permit is to be reopened, except that IDEM, OAQ, may provide a shorter time period in the case of an emergency. [326 IAC 2-8-8(c)]

B.16 Permit Renewal [326 IAC 2-8-3(h)]

(a) The application for renewal shall be submitted using the application form or forms prescribed by IDEM, OAQ and shall include the information specified in 326 IAC 2-8-3. Such information shall be included in the application for each emission unit at this source, except those emission units included on the trivial or insignificant activities list contained in 326 IAC 2-7-1(21) and 326 IAC 2-7-1(40). The renewal application does require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).

Request for renewal shall be submitted to:

Indiana Department of Environmental Management Permits Branch, Office of Air Quality 100 North Senate Avenue, P.O. Box 6015 Indianapolis, IN 46206-6015

- (b) Timely Submittal of Permit Renewal [326 IAC 2-8-3]
 - (1) A timely renewal application is one that is:
 - (A) Submitted at least nine (9) months prior to the date of the expiration of this permit; and
 - (B) If the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ, on or before the date it is due.
 - (2) If IDEM, OAQ upon receiving a timely and complete permit application, fails to issue or deny the permit renewal prior to the expiration date of this permit, this existing permit shall not expire and all terms and conditions shall continue in effect until the renewal permit has been issued or denied.
- (c) Right to Operate After Application for Renewal [326 IAC 2-8-9]

 If the Permittee submits a timely and complete application for renewal of this permit, the source's failure to have a permit is not a violation of 326 IAC 2-8 until IDEM, OAQ takes final action on the renewal application, except that this protection shall cease to apply if, subsequent to the completeness determination, the Permittee fails to submit by the deadline specified in writing by IDEM, OAQ, any additional information identified as needed to process the application.

B.17 Permit Amendment or Revision [326 IAC 2-8-10] [326 IAC 2-8-11.1]

- (a) Permit amendments and revisions are governed by the requirements of 326 IAC 2-8-10 or 326 IAC 2-8-11.1 whenever the Permittee seeks to amend or modify this permit.
- (b) Any application requesting an amendment or modification of this permit shall be submitted to:

Total Interior Systems - America, LLC Page 12 of 35
Princeton, Indiana F051-17729-00045

Permit Reviewer: ERG/SD

Indiana Department of Environmental Management Permits Branch, Office of Air Quality 100 North Senate Avenue, P.O. Box 6015 Indianapolis, Indiana 46206-6015

Any such application shall be certified by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).

- (c) The Permittee may implement the administrative amendment changes addressed in the request for an administrative amendment immediately upon submittal of the request. [326 IAC 2-8-10(b)(3)]
- (d) No permit amendment or modification is required for the addition, operation or removal of a nonroad engine, as defined in 40 CFR 89.2.

B.18 Operational Flexibility [326 IAC 2-8-15] [326 IAC 2-8-11.1]

- (a) The Permittee may make any change or changes at this source that are described in 326 IAC 2-8-15(b) through (d), without prior permit revision, if each of the following conditions is met:
 - (1) The changes are not modifications under any provision of Title I of the Clean Air Act;
 - (2) Any approval required by 326 IAC 2-8-11.1 has been obtained;
 - (3) The changes do not result in emissions which exceed the emissions allowable under this permit (whether expressed herein as a rate of emissions or in terms of total emissions);
 - (4) The Permittee notifies the:

Indiana Department of Environmental Management Permits Branch, Office of Air Quality 100 North Senate Avenue, P.O. Box 6015 Indianapolis, Indiana 46206-6015

and

United States Environmental Protection Agency, Region V Air and Radiation Division, Regulation Development Branch - Indiana (AR-18J) 77 West Jackson Boulevard Chicago, Illinois 60604-3590

in advance of the change by written notification at least ten (10) days in advance of the proposed change. The Permittee shall attach every such notice to the Permittee's copy of this permit; and

(5) The Permittee maintains records on-site which document, on a rolling five (5) year basis, all such changes and emissions trading that are subject to 326 IAC 2-8-15(b) through (d) and makes such records available, upon reasonable request, to public review.

Such records shall consist of all information required to be submitted to IDEM, OAQ, in the notices specified in 326 IAC 2-8-15(b)(2), (c)(1), and (d).

(b) Emission Trades [326 IAC 2-8-15(c)]

Total Interior Systems - America, LLC Page 13 of 35
Princeton, Indiana F051-17729-00045

Permit Reviewer: ERG/SD

The Permittee may trade increases and decreases in emissions in the source, where the applicable SIP provides for such emission trades without requiring a permit revision, subject to the constraints of Section (a) of this condition and those in 326 IAC 2-8-15(c).

(c) Alternative Operating Scenarios [326 IAC 2-8-15(d)]

The Permittee may make changes at the source within the range of alternative operating scenarios that are described in the terms and conditions of this permit in accordance with 326 IAC 2-8-4(7). No prior notification of IDEM, OAQ or U.S. EPA is required.

B.19 Permit Revision Requirement [326 IAC 2-8-11.1]

A modification, construction, or reconstruction is governed by the requirements of 326 IAC 2 and 326 IAC 2-8-11.1.

B.20 Inspection and Entry [326 IAC 2-8-5(a)(2)] [IC 13-14-2-2]] [IC 13-30-3-1]

Upon presentation of proper identification cards, credentials, and other documents as may be required by law, and subject to the Permittee's right under all applicable laws and regulations to assert that the information collected by the agency is confidential and entitled to be treated as such, the Permittee shall allow IDEM, OAQ, U.S. EPA, or an authorized representative to perform the following:

- Enter upon the Permittee's premises where a FESOP source is located, or emissions related activity is conducted, or where records must be kept under the conditions of this permit;
- (b) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, have access to and copy, at reasonable times, any records that must be kept under the conditions of this permit;
- (c) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, inspect, at reasonable times, any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under this permit;
- (d) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with this permit or applicable requirements; and
- (e) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, utilize any photographic, recording, testing, monitoring, or other equipment for the purpose of assuring compliance with this permit or applicable requirements.

B.21 Transfer of Ownership or Operational Control [326 IAC 2-8-10]

- (a) The Permittee must comply with the requirements of 326 IAC 2-8-10 whenever the Permittee seeks to change the ownership or operational control of the source and no other change in the permit is necessary.
- (b) Any application requesting a change in the ownership or operational control of the source shall contain a written agreement containing a specific date for transfer of permit responsibility, coverage and liability between the current and new Permittee. The application shall be submitted to:

Indiana Department of Environmental Management Permits Branch, Office of Air Quality 100 North Senate Avenue, P.O. Box 6015 Indianapolis, Indiana 46206-6015

The application which shall be submitted by the Permittee does require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).

Total Interior Systems - America, LLC Page 14 of 35
Princeton, Indiana F051-17729-00045

Permit Reviewer: ERG/SD

(c) The Permittee may implement administrative amendment changes addressed in the request for an administrative amendment immediately upon submittal of the request. [326 IAC 2-8-10(b)(3)]

B.22 Annual Fee Payment [326 IAC 2-7-19] [326 IAC 2-8-4(6)] [326 IAC 2-8-16] [326 IAC 2-1.1-7]

- (a) The Permittee shall pay annual fees to IDEM, OAQ, within thirty (30) calendar days of receipt of a billing. Pursuant to 326 IAC 2-7-19(b), if the Permittee does not receive a bill from IDEM, OAQ the applicable fee is due April 1 of each year.
- (b) Failure to pay may result in administrative enforcement action, or revocation of this permit.
- (c) The Permittee may call the following telephone numbers: 1-800-451-6027 or 317-233-4320 (ask for OAQ, I/M & Billing Section), to determine the appropriate permit fee.

Total Interior Systems - America, LLC Page 15 of 35
Princeton, Indiana F051-17729-00045

Permit Reviewer: ERG/SD

SECTION C SOURCE OPERATION CONDITIONS

Entire Source

Emissions Limitations and Standards [326 IAC 2-8-4(1)]

- C.1 Particulate Emission Limitations For Processes with Process Weight Rates Less Than One Hundred (100) pounds per hour [40 CFR 52 Subpart P][326 IAC 6-3-2]
 - (a) Pursuant to 40 CFR 52 Subpart P, particulate matter emissions from any process not already regulated by 326 IAC 6-1 or any New Source Performance Standard, and which has a maximum process weight rate less than 100 pounds per hour shall not exceed 0.551 pounds per hour.
 - (b) Pursuant to 326 IAC 6-3-2(e)(2), particulate emissions from any process not exempt under 326 IAC 6-3-1(b) or (c) which has a maximum process weight rate less than 100 pounds per hour and the methods in 326 IAC 6-3-2(b) through (d) do not apply shall not exceed 0.551 pounds per hour.

C.2 Overall Source Limit [326 IAC 2-8]

The purpose of this permit is to limit this source's potential to emit to less than major source levels for the purpose of Section 502(a) of the Clean Air Act.

- (a) Pursuant to 326 IAC 2-8:
 - (1) The potential to emit any regulated pollutant, except particulate matter (PM), from the entire source shall be limited to less than one-hundred (100) tons per twelve (12) consecutive month period. This limitation shall also make the requirements of 326 IAC 2-2 (Prevention of Significant Deterioration (PSD) not applicable);
 - (2) The potential to emit any individual hazardous air pollutant (HAP) from the entire source shall be limited to less than ten (10) tons per twelve (12) consecutive month period; and
 - (3) The potential to emit any combination of HAPs from the entire source shall be limited to less than twenty-five (25) tons per twelve (12) consecutive month period.
- (b) This condition shall include all emission points at this source including those that are insignificant as defined in 326 IAC 2-7-1(21). The source shall be allowed to add insignificant activities not already listed in this permit, provided the source's potential to emit does not exceed the above specified limits.
- (c) Section D of this permit contains independently enforceable provisions to satisfy this requirement.

C.3 Opacity [326 IAC 5-1]

Pursuant to 326 IAC 5-1-2 (Opacity Limitations), except as provided in 326 IAC 5-1-3 (Temporary Alternative Opacity Limitations), opacity shall meet the following, unless otherwise stated in this permit:

- (a) Opacity shall not exceed an average of forty percent (40%) in any one (1) six (6) minute averaging period as determined in 326 IAC 5-1-4.
- (b) Opacity shall not exceed sixty percent (60%) for more than a cumulative total of fifteen (15) minutes (sixty (60) readings as measured according to 40 CFR 60, Appendix A, Method 9 or fifteen (15) one (1) minute nonoverlapping integrated averages for a continuous opacity monitor) in a six (6) hour period.

Total Interior Systems - America, LLC Page 16 of 35
Princeton, Indiana F051-17729-00045

Permit Reviewer: ERG/SD

C.4 Open Burning [326 IAC 4-1] [IC 13-17-9]

The Permittee shall not open burn any material except as provided in 326 IAC 4-1-3, 326 IAC 4-1-4 or 326 IAC 4-1-6. The previous sentence notwithstanding, the Permittee may open burn in accordance with an open burning approval issued by the Commissioner under 326 IAC 4-1-4.1.

C.5 Incineration [326 IAC 4-2] [326 IAC 9-1-2(3)]

The Permittee shall not operate an incinerator or incinerate any waste or refuse except as provided in 326 IAC 4-2 and in 326 IAC 9-1-2.

C.6 Fugitive Dust Emissions [326 IAC 6-4]

The Permittee shall not allow fugitive dust to escape beyond the property line or boundaries of the property, right-of-way, or easement on which the source is located, in a manner that would violate 326 IAC 6-4 (Fugitive Dust Emissions).

C.7 Operation of Equipment [326 IAC 2-8-5(a)(4)]

Except as otherwise provided by statute, rule or in this permit, all air pollution control equipment listed in this permit and used to comply with an applicable requirement shall be operated at all times that the emission units vented to the control equipment are in operation.

- C.8 Asbestos Abatement Projects [326 IAC 14-10] [326 IAC 18] [40 CFR 61, Subpart M]

 The Permittee shall comply with the applicable requirements of 326 IAC 14-10, 326 IAC 18, and 40 CFR 61,140.
 - (a) Notification requirements apply to each owner or operator. If the combined amount of regulated asbestos containing material (RACM) to be stripped, removed or disturbed is at least 260 linear feet on pipes or 160 square feet on other facility components, or at least thirty-five (35) cubic feet on all facility components, then the notification requirements of 326 IAC 14-10-3 are mandatory. All demolition projects require notification whether or not asbestos is present.
 - (b) The Permittee shall ensure that a written notification is sent on a form provided by the Commissioner at least ten (10) working days before asbestos stripping or removal work or before demolition begins, per 326 IAC 14-10-3, and shall update such notice as necessary, including, but not limited to the following:
 - (1) When the amount of affected asbestos containing material increases or decreases by at least twenty percent (20%); or
 - (2) If there is a change in the following:
 - (A) Asbestos removal or demolition start date;
 - (B) Removal or demolition contractor; or
 - (C) Waste disposal site.
 - (c) The Permittee shall ensure that the notice is postmarked or delivered according to the guidelines set forth in 326 IAC 14-10-3(2).
 - (d) The notice to be submitted shall include the information enumerated in 326 IAC 14-10-3(3).

All required notifications shall be submitted to:

Indiana Department of Environmental Management Asbestos Section, Office of Air Quality 100 North Senate Avenue, P.O. Box 6015 Indianapolis, Indiana 46206-6015 Total Interior Systems - America, LLC Page 17 of 35
Princeton, Indiana F051-17729-00045

Permit Reviewer: ERG/SD

The notice shall include a signed certification from the owner or operator that the information provided in this notification is correct and that only Indiana licensed workers and project supervisors will be used to implement the asbestos removal project. The notifications do not require a certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).

(e) Procedures for Asbestos Emission Control

The Permittee shall comply with the applicable emission control procedures in 326 IAC 14-10-4 and 40 CFR 61.145(c). Per 326 IAC 14-10-1 emission control requirements are applicable for any removal or disturbance of RACM greater than three (3) linear feet on pipes or three (3) square feet on any other facility components or a total of at least 0.75 cubic feet on all facility components.

- (f) Demolition and Renovation
 - The Permittee shall thoroughly inspect the affected facility or part of the facility where the demolition or renovation will occur for the presence of asbestos pursuant to 40 CFR 61.145(a).
- (g) Indiana Accredited Asbestos Inspector
 The Permittee shall comply with 326 IAC 14-10-1(a) that requires the owner or operator,
 prior to a renovation/demolition, to use an Indiana Accredited Asbestos Inspector to
 thoroughly inspect the affected portion of the facility for the presence of asbestos. The
 requirement that the inspector be accredited is not federally enforceable.

Testing Requirements [326 IAC 2-8-4(3)]

C.9 Performance Testing [326 IAC 3-6]

(a) All testing shall be performed according to the provisions of 326 IAC 3-6 (Source Sampling Procedures), except as provided elsewhere in this permit, utilizing any applicable procedures and analysis methods specified in 40 CFR 51, 40 CFR 60, 40 CFR 61, 40 CFR 63, 40 CFR 75, or other procedures approved by IDEM, OAQ.

A test protocol, except as provided elsewhere in this permit, shall be submitted to:

Indiana Department of Environmental Management Compliance Data Section, Office of Air Quality 100 North Senate Avenue, P. O. Box 6015 Indianapolis, Indiana 46206-6015

no later than thirty-five (35) days prior to the intended test date. The protocol submitted by the Permittee does not require certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).

- (b) The Permittee shall notify IDEM, OAQ of the actual test date at least fourteen (14) days prior to the actual test date. The notification submitted by the Permittee does not require certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).
- (c) Pursuant to 326 IAC 3-6-4(b), all test reports must be received by IDEM, OAQ not later than forty-five (45) days after the completion of the testing. An extension may be granted by IDEM, OAQ, if the source submits to IDEM, OAQ, a reasonable written explanation not later than five (5) days prior to the end of the initial forty-five (45) day period.

Compliance Requirements [326 IAC 2-1.1-11]

Total Interior Systems - America, LLC Page 18 of 35
Princeton, Indiana F051-17729-00045

Permit Reviewer: ERG/SD

The commissioner may require stack testing, monitoring, or reporting at any time to assure compliance with all applicable requirements by issuing an order under 326 IAC 2-1.1-11. Any monitoring or testing shall be performed in accordance with 326 IAC 3 or other methods approved by the commissioner or the U. S. EPA.

Compliance Monitoring Requirements [326 IAC 2-8-4] [326 IAC 2-8-5(a)(1)]

C.11 Compliance Monitoring [326 IAC 2-8-4(3)] [326 IAC 2-8-5(a)(1)]

Unless otherwise specified in this permit, all monitoring and record keeping requirements not already legally required shall be implemented within ninety (90) days of permit issuance. If required by Section D, the Permittee shall be responsible for installing any necessary equipment and initiating any required monitoring related to that equipment. If due to circumstances beyond its control, that equipment cannot be installed and operated within ninety (90) days, the Permittee may extend the compliance schedule related to the equipment for an additional ninety (90) days provided the Permittee notifies:

Indiana Department of Environmental Management Compliance Branch, Office of Air Quality 100 North Senate Avenue, P.O. Box 6015 Indianapolis, Indiana 46206-6015

in writing, prior to the end of the initial ninety (90) day compliance schedule with full justification of the reasons for inability to meet this date.

The notification which shall be submitted by the Permittee does require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).

Unless otherwise specified in the approval for the new emissions unit, compliance monitoring for new emission units or emission units added through a permit revision shall be implemented when operation begins.

C.12 Monitoring Methods [326 IAC 3] [40 CFR 60] [40 CFR 63]

Any monitoring or testing performed required by Section D of this permit shall be performed according to the provisions of 326 IAC 3, 40 CFR 60, Appendix A, 40 CFR 60 Appendix B, 40 CFR 63 or other approved methods as specified in this permit.

Corrective Actions and Response Steps [326 IAC 2-8-4] [326 IAC 2-8-5(a)(1)]

C.13 Risk Management Plan [326 IAC 2-8-4] [40 CFR 68]

If a regulated substance, as defined in 40 CFR 68, is present at a source in more than a threshold quantity, the source must comply with the applicable requirements of 40 CFR 68.

C.14 Compliance Response Plan - Preparation, Implementation, Records, and Reports [326 IAC 2-8-4][326 IAC 2-8-5]

- (a) The Permittee is required to prepare a Compliance Response Plan (CRP) for each compliance monitoring condition of this permit. If a Permittee is required to have an Operation, Maintenance and Monitoring (OMM) Plan under 40 CFR 60/63, such plans shall be deemed to satisfy the requirements for a CRP for those compliance monitoring conditions. A CRP shall be submitted to IDEM, OAQ upon request. The CRP shall be prepared within ninety (90) days after issuance of this permit by the Permittee, supplemented from time to time by the Permittee, maintained on site, and is comprised of:
 - (1) Reasonable response steps that may be implemented in the event that a response step is needed pursuant to the requirements of Section D of this permit; and an expected timeframe for taking reasonable response steps.

Total Interior Systems - America, LLC Page 19 of 35
Princeton, Indiana F051-17729-00045

Permit Reviewer: ERG/SD

(2) If, at any time, the Permittee takes reasonable response steps that are not set forth in the Permittee's current Compliance Response Plan or Operation, Maintenance and Monitoring (OMM) Plan and the Permittee documents such response in accordance with subsection (e) below, the Permittee shall amend its Compliance Response Plan or Operation, Maintenance and Monitoring (OMM) Plan to include such response steps taken.

The OMM Plan shall be submitted within the time frames specified by the applicable 40 CFR60/63 requirement.

- (b) For each compliance monitoring condition of this permit, reasonable response steps shall be taken when indicated by the provisions of that compliance monitoring condition as follows:
 - (1) Reasonable response steps shall be taken as set forth in the Permittee's current Compliance Response Plan or Operation, Maintenance and Monitoring (OMM) Plan; or
 - (2) If none of the reasonable response steps listed in the Compliance Response Plan or Operation, Maintenance and Monitoring (OMM) Plan is applicable or responsive to the excursion, the Permittee shall devise and implement additional response steps as expeditiously as practical. Taking such additional response steps shall not be considered a deviation from this permit so long as the Permittee documents such response steps in accordance with this condition.
 - (3) If the Permittee determines that additional response steps would necessitate that the emissions unit or control device be shut down, and it will be 10 days or more until the unit or device will be shut down, then the permittee shall promptly notify the IDEM, OAQ of the expected date of the shut down, the status of the applicable compliance monitoring parameter with respect to normal, and the results of the actions taken up to the time of notification.
 - (4) Failure to take reasonable response steps shall be considered a deviation from the permit.
- (c) The Permittee is not required to take any further response steps for any of the following reasons:
 - (1) A false reading occurs due to the malfunction of the monitoring equipment and prompt action was taken to correct the monitoring equipment.
 - (2) The Permittee has determined that the compliance monitoring parameters established in the permit conditions are technically inappropriate, has previously submitted a request for an administrative amendment to the permit, and such request has not been denied.
 - (3) An automatic measurement was taken when the process was not operating.
 - (4) The process has already returned or is returning to operating within "normal" parameters and no response steps are required.
- (d) When implementing reasonable steps in response to a compliance monitoring condition, if the Permittee determines that an exceedance of an emission limitation has occurred, the Permittee shall report such deviations pursuant to Section B-Deviations from Permit Requirements and Conditions.

Total Interior Systems - America, LLC Page 20 of 35
Princeton, Indiana F051-17729-00045

Permit Reviewer: ERG/SD

(e) The Permittee shall record all instances when, in accordance with Section D, response steps are taken. In the event of an emergency, the provisions of 326 IAC 2-8-12 (Emergency Provisions) requiring prompt corrective action to mitigate emissions shall prevail.

(f) Except as otherwise provided by a rule or provided specifically in Section D, all monitoring as required in Section D shall be performed when the emission unit is operating, except for time necessary to perform quality assurance and maintenance activities.

C.15 Actions Related to Noncompliance Demonstrated by a Stack Test [326 IAC 2-8-4] [326 IAC 2-8-5]

- (a) When the results of a stack test performed in conformance with Section C Performance Testing, of this permit exceed the level specified in any condition of this permit, the Permittee shall take appropriate response actions. The Permittee shall submit a description of these response actions to IDEM, OAQ, within thirty (30) days of receipt of the test results. The Permittee shall take appropriate action to minimize excess emissions from the affected facility while the response actions are being implemented.
- (b) A retest to demonstrate compliance shall be performed within one hundred twenty (120) days of receipt of the original test results. Should the Permittee demonstrate to IDEM, OAQ that retesting in one-hundred and twenty (120) days is not practicable, IDEM, OAQ may extend the retesting deadline.
- (c) IDEM, OAQ reserves the authority to take any actions allowed under law in response to noncompliant stack tests.

The response action documents submitted pursuant to this condition do require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).

Record Keeping and Reporting Requirements [326 IAC 2-8-4(3)]

C.16 General Record Keeping Requirements [326 IAC 2-8-4(3)] [326 IAC 2-8-5]

- (a) Records of all required monitoring data, reports and support information required by this permit shall be retained for a period of at least five (5) years from the date of monitoring sample, measurement, report, or application. These records shall be physically present or electronically accessible at the source location for a minimum of three (3) years. The records may be stored elsewhere for the remaining two (2) years as long as they are available upon request. If the Commissioner makes a request for records to the Permittee, the Permittee shall furnish the records to the Commissioner within a reasonable time.
- (b) Unless otherwise specified in this permit, all record keeping requirements not already legally required shall be implemented within ninety (90) days of permit issuance.

C.17 General Reporting Requirements [326 IAC 2-8-4(3)(C)] [326 IAC 2-1.1-11]

- (a) The source shall submit the attached Quarterly Deviation and Compliance Monitoring Report or its equivalent. Any deviation from permit requirements, the date(s) of each deviation, the cause of the deviation, and the response steps taken must be reported. This report shall be submitted within thirty (30) days of the end of the reporting period. The Quarterly Deviation and Compliance Monitoring Report shall include the certification by the "authorized individual" as defined by 326 IAC2-1.1-1(1).
- (b) The report required in (a) of this condition and reports required by conditions in Section D of this permit shall be submitted to:

Indiana Department of Environmental Management Compliance Data Section, Office of Air Quality 100 North Senate Avenue, P. O. Box 6015 Total Interior Systems - America, LLC Page 21 of 35
Princeton, Indiana F051-17729-00045

Permit Reviewer: ERG/SD

Indianapolis, Indiana 46206-6015

- (c) Unless otherwise specified in this permit, any notice, report, or other submission required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ, on or before the date it is due.
- (d) Unless otherwise specified in this permit, any reports required in Section D of this permit shall be submitted within thirty (30) days of the end of the reporting period. The reports do require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).
- (e) The first report covered the period commencing on the date of issuance of the original FESOP and ended on the last day of the reporting period. All subsequent reporting periods shall be based on calendar years.

Stratospheric Ozone Protection

C.18 Compliance with 40 CFR 82 and 326 IAC 22-1

Pursuant to 40 CFR 82 (Protection of Stratospheric Ozone), Subpart F, except as provided for motor vehicle air conditioners in Subpart B, the Permittee shall comply with the standards for recycling and emissions reduction:

- (a) Persons opening appliances for maintenance, service, repair or disposal must comply with the required practices pursuant to 40 CFR 82.156
- (b) Equipment used during the maintenance, service, repair or disposal of appliances must comply with the standards for recycling and recovery equipment pursuant to 40 CFR 82.158.
- (c) Persons performing maintenance, service, repair or disposal of appliances must be certified by an approved technician certification program pursuant to 40 CFR 82.161.

Princeton, Indiana Permit Reviewer: ERG/SD

SECTION D.1 FACILITY OPERATION CONDITIONS

Facility Description [326 IAC 2-8-4(10)]

(a) Three (3) spray booths (identified as EU 02, 03 and 04), using three (3) HVLP guns, each with a maximum throughput rate of 8.64 gallons of coating per hour, using dry filters for over spray control and exhausting at stacks ID 02, 03 and 04.

Page 22 of 35

F051-17729-00045

(b) One (1) red spot spray booth (identified as EU 01), using one (1) HVLP gun, with a maximum throughput rate of 0.41 gallons of coating per hour, using dry filters for over spray control and exhausting at stack ID 01.

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

Emission Limitations and Standards

D.1.1 Hazardous Air Pollutants and Volatile Organic Compounds [326 IAC 2-8-4]

Pursuant to 326 IAC 2-8-4:

- (a) The amount of any single HAP delivered to the surface coating operation consisting of four (4) spray booths plus the amount of any single HAP used for clean-up shall be limited to less than ten (10) tons per twelve (12) consecutive months with compliance determined at the end of each month.
- (b) The amount of any combination of HAPs delivered to the surface coating operation consisting of four (4) spray booths shall be limited to less than twenty-five (25) tons per twelve (12) consecutive month period with compliance determined at the end of each month.
- (c) The potential to emit VOC from the entire source is less than one hundred (100) tons per year. Any change or modification which may increase the potential to emit VOC from the entire source to greater than one hundred (100) tons per year must be approved by the IDEM, OAQ.

Compliance with the above limits renders 326 IAC 2-7 (Part 70 Program) not applicable to the source.

D.1.2 Volatile Organic Compounds (VOCs) [326 IAC 8-1-6]

The VOC delivered to the applicator of the three (3) spray booths (identified as EU 02, 03 and 04) shall each be limited to less than twenty-five (25) tons per twelve (12) consecutive month period with compliance determined at the end of each month. Therefore, the best available control technology (BACT) requirement in 326 IAC 8-1-6 (New Facilities: General Reduction Requirements) does not apply.

D.1.3 Particulate Matter (PM) [40 CFR Subpart P]

Pursuant to 40 CFR Subpart P, the particulate emissions from the surface coating operation consisting of four (4) spray booths shall not exceed the pound per hour emission rate established as E in the following formula:

Interpolation of the data for the process weight rate up to sixty thousand (60,000) pounds per hour shall be accomplished by use of the equation:

 $E = 4.10 P^{0.67}$ where E = rate of emission in pounds per hour; and P = process weight rate in tons per hour

Total Interior Systems - America, LLC Page 23 of 35
Princeton, Indiana F051-17729-00045

Permit Reviewer: ERG/SD

D.1.4 Particulate [326 IAC 6-3-2(d)]

Pursuant to 326 IAC 6-3-2(d), particulate from the surface coating operation consisting of four (4) spray booths shall be controlled by a dry particulate filters, and the Permittee shall operate the control device in accordance with manufacturer's specifications.

D.1.5 Preventive Maintenance Plan [326 IAC 2-8-4(9)]

A Preventive Maintenance Plan, in accordance with Section B - Preventive Maintenance Plan, of this permit, is required for these facilities and their control device.

Compliance Determination Requirements

D.1.6 HAP and VOC Emissions

Compliance with the HAP and VOC content and usage limitations contained in Condition D.1.1 and D.1.2 shall be determined pursuant to 326 IAC 8-1-4(a)(3) and 326 IAC 8-1-2(a) by preparing or obtaining from the manufacturer the copies of the "as supplied" and "as applied" VOC data sheets. IDEM, OAQ, reserves the authority to determine compliance using Method 24 in conjunction with the analytical procedures specified in 326 IAC 8-1-4.

Compliance Monitoring Requirements [326 IAC 2-8-4] [326 IAC 2-8-5(a)(1)]

D.1.7 Monitoring

- (a) Daily inspections shall be performed to verify the placement, integrity and particle loading of the filters. To monitor the performance of the dry filters, weekly observations shall be made of the overspray from the four (4) surface coating booth stacks (stacks ID 01, 02, 03 and 04) while one or more of the booths are in operation. The Compliance Response Plan shall be followed whenever a condition exists which should result in a response step. Preparation, Implementation, Records, and Reports in accordance with Section C Compliance Response Plan Preparation, Implementation, Records, and Reports, shall be considered a violation of this permit.
- (b) Monthly inspections shall be performed of the coating emissions from the stack and the presence of overspray on the rooftops and the nearby ground. The Compliance Response Plan for this unit shall contain troubleshooting contingency and response steps for when a noticeable change in overspray emission, or evidence of overspray emission is observed. The Compliance Response Plan shall be followed whenever a condition exists which should result in a response step. Failure to take response steps in accordance with Section C Compliance Response Plan Preparation, Implementation, Records, and Reports, shall be considered a violation of this permit.
- (c) Additional inspections and preventive measures shall be performed as prescribed in the Preventive Maintenance Plan.

Record Keeping Requirements [326 IAC 2-8-4(3)] [326 IAC 2-8-16]

D.1.8 Record Keeping Requirements

- (a) To document compliance with Conditions D.1.1 and D.1.2, the Permittee shall maintain records in accordance with (1) through (4) below. Records maintained for (1) through (4) shall be taken monthly and shall be complete and sufficient to establish compliance with the HAP and VOC usage limits and the HAP and VOC emission limits established in Condition D.1.1 and D.1.2.
 - (1) The VOC and HAP contents of each coating material and solvent used;
 - (2) The amount of coating material and solvent less water used on a monthly basis.
 - (A) Records shall include purchase orders, invoices, and material safety data sheets (MSDS) necessary to verify the type and amount used.

Total Interior Systems - America, LLC Page 24 of 35
Princeton, Indiana F051-17729-00045

Permit Reviewer: ERG/SD

(B) Solvent usage records shall differentiate between those added to coatings and those used as cleanup solvents.

- (3) The total HAP and VOC usage for each month; and
- (4) The weight of VOC and HAP usage for each compliance period.
- (b) To document compliance with Condition D.1.7, the Permittee shall maintain a log of weekly overspray observations, daily and monthly inspections, and those additional inspections prescribed by the Preventive Maintenance Plan.
- (c) To document compliance with Condition D.1.5, the Permittee shall maintain records of any additional inspections prescribed by the Preventive Maintenance Plan.
- (d) All records shall be maintained in accordance with Section C General Record Keeping Requirements, of this permit.

D.1.9 Reporting Requirements

A quarterly summary of the information to document compliance with Condition D.1.1 and D.1.2 shall be submitted to the address listed in Section C - General Reporting Requirements, of this permit, using the reporting forms located at the end of this permit, or their equivalent, within thirty (30) days after the end of the quarter period being reported. The report submitted by the Permittee does require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).

Total Interior Systems - America, LLC Page 25 of 35 Princeton, Indiana F051-17729-00045

Permit Reviewer: ERG/SD

SECTION D.2

FACILITY OPERATION CONDITIONS

Facility Description [326 IAC 2-8-4(10)]

Insignificant Activities

(a) One (1) 1,000 kW diesel emergency generator burning No. 2 fuel oil.

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

Emission Limitations and Standards [326 IAC 2-8-4(1)]

There are no specifically applicable requirements for this facility.

Total Interior Systems - America, LLC Page 26 of 35 Princeton, Indiana F051-17729-00045

Permit Reviewer: ERG/SD

INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT OFFICE OF AIR QUALITY

FEDERALLY ENFORCEABLE STATE OPERATING PERMIT (FESOP) CERTIFICATION

Source Name: Total Interiors Systems - America, LLC

Source Address: Rural Route 1, Box 101 County Road 100, Princeton, Indiana 47670 Mailing Address: Rural Route 1, Box 101 County Road 100, Princeton, Indiana 47670

FESOP No.: F051-17729-00045

	This certification shall be included when submitting monitoring, testing reports/results or other documents as required by this permit.
	Please check what document is being certified:
9	Annual Compliance Certification Letter
9	Test Result (specify)
9	Report (specify)
9	Notification (specify)
9	Affidavit (specify)
9	Other (specify)
	tify that, based on information and belief formed after reasonable inquiry, the statements and information ne document are true, accurate, and complete.
Sigr	nature:
Prin	ted Name:
Title	/Position:
Date	e:

Total Interior Systems - America, LLC Princeton, Indiana

Page 27 of 35 F051-17729-00045 Permit Reviewer: ERG/SD

INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT OFFICE OF AIR QUALITY

COMPLIANCE BRANCH P.O. Box 6015 100 North Senate Avenue

Indianapolis, Indiana 46206-6015 Phone: 317-233-5674

Fax: 317-233-5967

FEDERALLY ENFORCEABLE STATE OPERATING PERMIT (FESOP) **EMERGENCY OCCURRENCE REPORT**

Source Name: Total Interiors Systems - America, LLC

Source Address: Rural Route 1, Box 101 County Road 100, Princeton, Indiana 47670 Rural Route 1, Box 101 County Road 100, Princeton, Indiana 47670 Mailing Address:

FESOP No.: F051-17729-00045

This form consists of 2	pages
-------------------------	-------

Page 1 of 2

9 This is an emergency as defined in 326 IAC 2-7-1(12)

CThe Permittee must notify the Office of Air Quality (OAQ), within four (4) business hours (1-800-

451-6027 or 317-233-5674, ask for Compliance Section); and CThe Permittee must submit notice in writing or by facsimile within two (2) working days

(Facsimile Number: 317-233-5967), and follow the other requirements of 326 IAC 2-7-16

if any of the following are not applicable, mark N/A
Facility/Equipment/Operation:
Control Equipment:
Permit Condition or Operation Limitation in Permit:
Description of the Emergency:
Describe the cause of the Emergency:

Total Interior Systems - America, LLC Princeton, Indiana Permit Reviewer: ERG/SD

If any of the following are not applicable, mark N/A

Page 28 of 35 F051-17729-00045

Page 2 of 2

Date/Time Emergency started:
Date/Time Emergency was corrected:
Was the facility being properly operated at the time of the emergency? Y N Describe:
Type of Pollutants Emitted: TSP, PM-10, SO ₂ , VOC, NO _X , CO, Pb, other:
Estimated amount of pollutant(s) emitted during emergency:
Describe the steps taken to mitigate the problem:
Describe the corrective actions/response steps taken:
Describe the measures taken to minimize emissions:
If applicable, describe the reasons why continued operation of the facilities are necessary to prevent imminent injury to persons, severe damage to equipment, substantial loss of capital investment, or loss of product or raw materials of substantial economic value:
Form Completed by: Title / Position: Date: Phone:

A certification is not required for this report.

Total Interior Systems - America, LLC Princeton, Indiana

Permit Reviewer: ERG/SD

COMPLIANCE DATA SECTION

Page 29 of 35

F051-17729-00045

FESOP Quarterly Report

Source Name: Total Interiors Systems - America, LLC

Source Address: Rural Route 1, Box 101 County Road 100, Princeton, Indiana 47670 Mailing Address: Rural Route 1, Box 101 County Road 100, Princeton, Indiana 47670

FESOP No.: F051-17729-00045

Facility: Spray Booth (Identified as EU 02)

Parameter: VOC

Limit: Less than twenty-five (25) tons per twelve (12) consecutive month period, with

compliance determined at the end of each month

|--|

	Column 1	Column 2	Column 1 + Column 2
Month	VOC	VOC	VOC
	This Month	Previous 11 Months	12 Month Total
Month 1			
Month 2			
Month 3			

9	No deviation	occurred in this q	uarter.	
9		occurred in this quass been reported or		
Title	_			

Total Interior Systems - America, LLC Princeton, Indiana

Phone:

Permit Reviewer: ERG/SD

Page 30 of 35 F051-17729-00045

INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT OFFICE OF AIR QUALITY COMPLIANCE DATA SECTION

	FESOP	Quarterly Report			
Source Name: Source Address: Mailing Address: FESOP No.: Facility: Parameter: Limit: Total Interiors Systems - America, LLC Rural Route 1, Box 101 County Road 100, Princeton, Indiana 47670 Rural Route 1, Box 101 County Road 100, Princeton, Indiana 47670 F051-17729-00045 Spray Booth (Identified as EU 03) VOC Limit: Less than twenty-five (25) tons per twelve (12) consecutive month period, with compliance determined at the end of each month YEAR: Total Interiors Systems - America, LLC Rural Route 1, Box 101 County Road 100, Princeton, Indiana 47670 F051-17729-00045 Spray Booth (Identified as EU 03) VOC Less than twenty-five (25) tons per twelve (12) consecutive month period, with					
	Column 1	Column 2	Column 1 + Column 2		
Month	VOC	VOC	VOC		
	This Month	Previous 11 Months	12 Month Total		
Month 1					
Month 2					
Month 3					
Titl	e / Position: nature:	his quarter.			

Total Interior Systems - America, LLC Princeton, Indiana Permit Reviewer: ERG/SD

Phone:

Page 31 of 35 F051-17729-00045

INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT OFFICE OF AIR QUALITY COMPLIANCE DATA SECTION

FESOP Quarterly Report				
Source Name: Source Address: Mailing Address: FESOP No.: Facility: Parameter: VOC Limit: Total Interiors Systems - America, LLC Rural Route 1, Box 101 County Road 100, Princeton, Indiana 47670 Rural Route 1, Box 101 County Road 100, Princeton, Indiana 47670 F051-17729-00045 Spray Booth (Identified as EU 04) VOC Less than twenty-five (25) tons per twelve (12) consecutive month period, with compliance determined at the end of each month YEAR:				
			<u> </u>	
Month	Column 1	Column 2	Column 1 + Column 2	
	VOC	VOC	VOC	
	This Month	Previous 11 Months	12 Month Total	
Month 1				
Month 2				
Month 3				
Title	e / Position:	nis quarter.		

Phone:

Page 32 of 35 F051-17729-00045

INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT OFFICE OF AIR QUALITY COMPLIANCE DATA SECTION

COMPLIANCE DATA SECTION					
	FESOP	Quarterly Report			
Source Name: Source Address: Mailing Address: FESOP No.: Facility: Parameter: Limit:	Name: Total Interiors Systems - America, LLC Address: Rural Route 1, Box 101 County Road 100, Princeton, Indiana 47670 Address: Rural Route 1, Box 101 County Road 100, Princeton, Indiana 47670 No.: F051-17729-00045 Surface Coating Operation				
	YEAR	:			
	Column 1	Column 2	Column 1 + Column 2		
Month	Single HAP	Single HAP	Single HAP		
	This Month	Previous 11 Months	12 Month Total		
Month 1					
Month 2					
Month 3					
Title	omitted by: e / Position: nature:	·			

Total Interior Systems - America, LLC Princeton, Indiana Permit Reviewer: ERG/SD Page 33 of 35 F051-17729-00045

OFFICE OF AIR QUALITY COMPLIANCE DATA SECTION

FESOP Quarterly Report

Source Name: Total Interiors Systems - America, LLC

Source Address: Rural Route 1, Box 101 County Road 100, Princeton, Indiana 47670 Mailing Address: Rural Route 1, Box 101 County Road 100, Princeton, Indiana 47670

FESOP No.: F051-17729-00045

Facility: Surface Coating Operation Parameter: Combination of HAPs

Limit: Less than twenty-five (25) tons per twelve (12) consecutive month period, with

compliance determined at the end of each month.

Month	Column 1	Column 2	Column 1 + Column 2
	Combination of HAPs	Combination of HAPs	Combination of HAPs
	This Month	Previous 11 Months	12 Month Total
Month 1			
Month 2			
Month 3			

9	No deviation	n occurred in this quarter.			
9		Deviation/s occurred in this quarter. Deviation has been reported on:			
Title	mitted by: / Position: nature:				
Pho	ne.				

Total Interior Systems - America, LLC

Princeton, Indiana Permit Reviewer: ERG/SD

INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT OFFICE OF AIR QUALITY **COMPLIANCE DATA SECTION**

Page 34 of 35

F051-17729-00045

FEDERALLY ENFORCEABLE STATE OPERATING PERMIT (FESOP) QUARTERLY DEVIATION AND COMPLIANCE MONITORING REPORT

Source Name: Total Interiors Systems - America, LLC Source Address: Rural Route 1, Box 101 County Road 100, Princeton, Indiana 47670 Rural Route 1, Box 101 County Road 100, Princeton, Indiana 47670 Mailing Address: FESOP No.: F051-17729-00045 Months: _____ to ____ Year: _____ Page 1 of 2 This report shall be submitted quarterly based on a calendar year. Any deviation from the requirements, the date(s) of each deviation, the probable cause of the deviation, and the response steps taken must be reported. Deviations that are required to be reported by an applicable requirement shall be reported according to the schedule stated in the applicable requirement and do not need to be included in this report. Additional pages may be attached if necessary. If no deviations occurred, please specify in the box marked "No deviations occurred this reporting period". 9 NO DEVIATIONS OCCURRED THIS REPORTING PERIOD. 9 THE FOLLOWING DEVIATIONS OCCURRED THIS REPORTING PERIOD **Permit Requirement** (specify permit condition #) Date of Deviation: **Duration of Deviation:** Number of Deviations: **Probable Cause of Deviation:** Response Steps Taken: **Permit Requirement** (specify permit condition #) Date of Deviation: **Duration of Deviation: Number of Deviations:** Probable Cause of Deviation: Response Steps Taken:

Page 35 of 35 F051-17729-00045

Page 2 of 2

	, ago 2 0, 1					
Permit Requirement (specify permit condition #)						
Date of Deviation:	Duration of Deviation:					
Number of Deviations:						
Probable Cause of Deviation:						
Response Steps Taken:						
Permit Requirement (specify permit condition #)						
Date of Deviation:	Duration of Deviation:					
Number of Deviations:						
Probable Cause of Deviation:	Probable Cause of Deviation:					
Response Steps Taken:						
Permit Requirement (specify permit condition #)						
Date of Deviation:	Duration of Deviation:					
Number of Deviations:						
Probable Cause of Deviation:						
Response Steps Taken:						
Form Completed By:						
Title/Position:						
Date:						
Phone:						

Indiana Department of Environmental Management Office of Air Quality

Technical Support Document (TSD) for a Federally Enforceable State Operating Permit (FESOP)

Source Background and Description

Source Name: Total Interior Systems - America, LLC

Source Location: Rural Route 1, Box 101 County Road 100, Princeton, Indiana 47670

County: Gibson SIC Code: 2396

Operation Permit No.: 051-17729-00045

Permit Reviewer: ERG/SD

The Office of Air Quality (OAQ) has reviewed a FESOP application from Total Interior Systems - America, LLC relating to the operation of a vehicle door panel manufacturing plant.

Permitted Emission Units and Pollution Control Equipment

The source consists of the following permitted emission units and pollution control devices:

- (a) Three (3) spray booths (identified as EU 02, 03 and 04), using three (3) HVLP guns, each with a maximum throughput rate of 8.64 gallons of coating per hour, using dry filters for over spray control and exhausting at stacks ID 02, 03 and 04.
- (b) One (1) red spot spray booth (identified as EU 01), using one (1) HVLP gun, with a maximum throughput rate of 0.41 gallons of coating per hour, using dry filters for over spray control and exhausting at stack ID 01.

Note: The one (1) red spot spray booth (identified as EU01) was constructed in 2003. The source limited the potential to emit of VOC and HAP from this unit by complying with 326 IAC 2-9.2.5 (Industrial or Commercial Surface Coating Operation). According to 326 IAC 2-9-1, a source issued a Source Specific Operating Agreement (SSOA) is not subject to 326 IAC 2-5.1 (Construction of New Sources) or 326 IAC 2-7 (Part 70 Permit Program), provided the SSOA limits the source's potential to emit below the applicability thresholds for 326 IAC 2-5.1 or 326 IAC 2-7.

Unpermitted Emission Units and Pollution Control Equipment

There are no unpermitted emission units operating at this source.

New Emission Units and Pollution Control Equipment

There are no new emission units or pollution control equipment receiving approval.

Insignificant Activities

This source also consists of the following insignificant activity, as defined in 326 IAC 2-7-1(21).

(a) One (1) 1,000 kW emergency generator burning No. 2 fuel oil.

Existing Approvals

The source has been operating under previous approvals including, but not limited to, the following:

(a) SSOA051-15689-00045, issued on March 25, 2002.

All terms and conditions of previous permits issued pursuant to permitting programs approved into the state implementation plan have been either incorporated as originally stated, revised, or deleted by this permit. All previous registrations and permits are superseded by this permit.

The following terms and conditions from previous approvals have been determined no longer applicable; therefore, were not incorporated into this permit:

(a) All conditions pursuant to 326 IAC 2-9-2.5 (Surface Coating or Graphic Arts Operation) as permitted under SSOA 051-15689-00045, issued on March 25, 2002.

Reason not incorporated: The source has now requested to be permitted under the provisions of 326 IAC 2-8 (Federally Enforceable State Operating Permit (FESOP)) since the future production volumes will exceed SSOA permit limit. Therefore, all conditions pursuant to 326 IAC 2-9-2.5 (Surface Coating or Graphic Arts Operation) were removed.

Enforcement Issue

There are no enforcement actions pending.

Recommendation

The staff recommends to the Commissioner that the FESOP be approved. This recommendation is based on the following facts and conditions:

Unless otherwise stated, information used in this review was derived from the application and additional information submitted by the applicant.

An administratively complete FESOP application for the purposes of this review was received on May 14, 2003.

Emission Calculations

See Appendix A of this document for detailed emissions calculations (Appendix A, pages 1 through 5).

Potential To Emit for the Source

Pursuant to 326 IAC 2-1.1-1(16), Potential to Emit is defined as "the maximum capacity of a stationary source to emit any air pollutant under its physical and operational design. Any physical or operational limitation on the capacity of a source to emit an air pollutant, including air pollution control equipment and restrictions on hours of operation or type or amount of material combusted, stored, or processed shall be treated as part of its design if the limitation is enforceable by the U. S. EPA."

Permit Reviewer: ERG/SD

This table reflects the PTE before controls. Control equipment is not considered federally enforceable until it has been required in a federally enforceable permit.

Pollutant	Potential To Emit (tons/year)					
PM	8.13					
PM10	8.13					
SO ₂	1.26					
VOC	84.9					
СО	0.03					
NO _x	0.12					

Note: For the purpose of determining Title V applicability for particulates, PM10, not PM, is the regulated pollutant in consideration.

HAPs	Potential To Emit (tons/year)
Xylene	1.21
1-Butanol	0.06
Methyl Alcohol	0.01
Ethylbenzene	0.21
4-Methyl-2-Pentanume	0.31
Toluene	18.0
Hexane	19.5
Ethyl Acetate	39.1
Total HAPs	78.3

- (a) The potential to emit (as defined in 326 IAC 2-1.1-1(16)) of any single HAP is equal to or greater than ten (10) tons per year and the potential to emit (as defined in 326 IAC 2-7-1(29)) of a combination HAPs is greater than or equal to twenty-five (25) tons per year. Therefore, the source is subject to the provisions of 326 IAC 2-7.
- (b) Pursuant to 326 IAC 2-8, this source, otherwise required to obtain a Title V permit, has agreed to accept a permit with federally enforceable limits that restrict PTE to below Title V emission levels. Therefore, this source will be issued a Federally Enforceable State Operating Permit (FESOP).
- (c) Fugitive Emissions
 Since this type of operation is not one of the twenty-eight (28) listed source categories
 under 326 IAC 2-2 and since there are no applicable New Source Performance Standards
 that were in effect on August 7, 1980, the fugitive emissions are not counted toward

determination of PSD and Emission Offset applicability.

Potential to Emit After Issuance

The table below summarizes the potential to emit, reflecting all limits, of the significant emission units after controls. The control equipment is considered federally enforceable only after issuance of this Federally Enforceable State Operating Permit.

Permit Reviewer: ERG/SD

		Potential to Emit (tons/year)								
Emission Unit	PM	PM10	SO ₂	VOC	СО	NO _X	HAPs			
Emergency Generator	0.01	0.01	1.26	0.002	0.03	0.12	Negligible			
Surface Coating Operation	8.12	8.12	-	less than 84.9		1	See footnote a			
Total Emissions	8.13	8.13	1.26	less than 84.9	0.03	0.12	See footnote a			

^a Less than 10 tons per year for a single HAP and less than 25 tons per year for any combination of HAPs.

County Attainment Status

The source is located in Gibson County.

Pollutant	Status				
PM10	Attainment				
SO ₂	Unclassifiable				
NO_2	Attainment				
Ozone	Attainment				
CO	Attainment				
Lead	Attainment				

- (a) Volatile organic compounds (VOC) are precursors for the formation of ozone. Therefore, VOC emissions are considered when evaluating the rule applicability relating to the ozone standards. Gibson County has been designated as severe nonattainment for ozone.
- (b) Gibson County has been classified as attainment or unclassifiable for all criteria pollutants. Therefore, these emissions were reviewed pursuant to the requirements for Prevention of Significant Deterioration (PSD), 326 IAC 2-2.

Federal Rule Applicability

- (a) The requirements of 40 CFR Part 64, Compliance Assurance Monitoring are not applicable because this source has accepted limitations on its potential to emit and agreed to operate under a Federally Enforceable State Operating Permit.
- (b) There are no New Source Performance Standards (NSPS)(326 IAC 12 and 40 CFR Part 60) applicable to this source.
- (c) There are no National Emission Standards for Hazardous Air Pollutants (NESHAPs) (326 IAC 14 and 40 CFR Part 63) applicable to this source.
- (d) The requirements of Section 112(j) of the Clean Air Act (40 CFR Part 63.50 through 63.56) are not applicable to this source because although the source has potential to emit of any single HAP above ten (10) tons per year and any combination of HAPs above twenty-five (25) tons per year, the source has agreed to operate under a Federally Enforceable State Operating Permit (FESOP) which limits their HAP emissions to below the major source threshold levels.

Total Interior Systems - America, LLC 5 of 8
Princeton, Indiana F051-17729-00045

Permit Reviewer: ERG/SD

326 IAC 2-2 (Prevention of Significant Deterioration (PSD))

This source was constructed in 2002 and is not one (1) of the twenty-eight (28) source categories defined in 326 IAC 2-2-1(p)(1). At the time of its construction, the potential to emit of each criteria pollutant before control was less than two hundred and fifty (250) tons per year. The source was modified in 2003 to add a spray booth and one (1) 1000 kW emergency generator. After these modifications, the potential to emit of each criteria pollutant before control remained less than two hundred and fifty (250) tons per year. Therefore, the source is a minor source under PSD and the requirements of 326 IAC 2-2 are not applicable.

326 IAC 2-6 (Emission Reporting)

This source is located in Gibson County and the potential to emit of all criteria pollutants is less than one hundred (100) tons per year. Therefore, 326 IAC 2-6 does not apply

326 IAC 5-1 (Opacity Limitations)

Pursuant to 326 IAC 5-1-2 (Opacity Limitations), except as provided in 326 IAC 5-1-3 (Temporary Alternative Opacity Limitations), opacity shall meet the following, unless otherwise stated in this permit:

- (a) Opacity shall not exceed an average of forty percent (40%) in any one (1) six (6) minute averaging period as determined in 326 IAC 5-1-4.
- (b) Opacity shall not exceed sixty percent (60%) for more than a cumulative total of fifteen (15) minutes (sixty (60) readings as measured according to 40 CFR 60, Appendix A, Method 9 or fifteen (15) one (1) minute nonoverlapping integrated averages for a continuous opacity monitor) in a six (6) hour period.

326 IAC 2-4.1 (New Sources of Hazardous Air Pollutants)

The source was constructed in 2002 and consisted of three (3) spray booths utilized for surface coating operation, for which they were issued an SSOA under 326 IAC 2-9-2.5 (Surface Coating and Graphic Arts Operation) on March 13, 2002. Operation of the three (3) spray booths under the SSOA kept the potential to emit of any single HAP and the potential to emit of any combination of HAPs less than 10 and 25 tons per year, respectively. The source plans to increase production volumes after the issuance of this permit, therefore, the potential to emit of HAPs will be greater than 10 and 25 tons per year for a single HAP and any combination of HAPs, respectively. However, the source has requested to operate under the provisions of 326 IAC 2-8, the potential to emit of a single HAP shall be limited to less than 10 tons per year and the potential to emit of any combination of HAPs shall be limited to less than twenty-five (25) tons per year, respectively. Therefore, the requirements of 326 IAC 2-4.1 are not applicable to this source.

326 IAC 2-8-4 (FESOP)

The potential to emit of VOC is less than one hundred (100) tons per year. However, the potential to emit a single HAP (Toluene, Hexane, and Ethyl Acetate) is greater than ten (10) tons per year and any combination of HAPs from the entire source is greater than twenty-five (25) tons per year.

Pursuant to 326 IAC 2-8-4:

- (a) In order to limit the source to less than ten (10) tons per year of any single HAP, the amount of any single HAP delivered to the surface coating operation consisting of four (4) spray booths plus the amount of any single HAP used for clean-up shall be limited to less than ten (10) tons per twelve (12) consecutive month period with compliance determined at the end of each month.
- (b) In order to limit the entire source to less than twenty-five (25) tons per year of any combination of HAPs, the amount of any combination of HAPs delivered to the surface

Total Interior Systems - America, LLC Princeton, Indiana F051-17729-00045

Permit Reviewer: ERG/SD

coating operation consisting of four (4) spray booths shall be limited to less than twentyfive (25) tons per twelve (12) consecutive month period with compliance determined at the end of each month.

6 of 8

(c) The potential to emit VOC from the entire source is less than one hundred (100) tons per year. Any change or modification which may increase the potential emissions of VOC from the entire source to greater than one hundred (100) tons per year must be approved by the IDEM, OAQ.

These limits ensures that any combination of HAP emissions from the entire source will be less than twenty-five (25) tons per year; and any single HAP emission will be less than 10 tons per year. These limits renders 326 IAC 2-7 (Part 70 Permit Program) not applicable to the source.

State Rule Applicability - Surface Coating Operation

326 IAC 8-1-6 (General Reduction Requirements for VOC Emissions)

The potential emissions of VOC from each of the three (3) spray booths (identified as EU 02, 03, and 04) used for coating polypropylene plastic based vehicle door panels, are less than twenty-five (25) tons per year before the increase in production. After the increase in production, the potential emissions will be greater than 25 tons per year. The three (3) spray booths are considered as three (3) separate lines since the product can go to either of the three (3) booths for coating. Therefore, the VOC content delivered to the applicator of the three (3) spray booths shall each be limited to less than twenty-five (25) tons per twelve (12) consecutive month period with compliance determined at the end of each month. Therefore, the requirements of 326 IAC 8-1-6 (New Facilities: General Reduction Requirements) do not apply.

The potential emissions of VOC from spray booth (identified as EU01) is less than twenty-five (25) tons per year. Therefore, 326 IAC 8-1-6 do not apply to this unit.

326 IAC 8-2-2 (Automobile & Light Duty Truck Coating Operation)

This source is not subject to the requirements of 326 IAC 8-2-2 ((Automobile & Light Duty Truck Coating Operation) because this source does not operate an automotive and light duty truck assembly plant. It operates a surface coating operation for vehicle door panels.

326 IAC 6-3-2 (Process Operations)

On June 12, 2002, revisions to 326 IAC 6-3 (Particulate Emission Limitations for Manufacturing Processes) became effective; this rule was previously referred to as 326 IAC 6-3 (Process Operations). As of the date this permit is being issued, these revisions have not been approved by EPA into the Indiana State Implementation Plan (SIP); therefore, the following requirement from the previous version of 326 IAC 6-3 (Process Operations) which has been approved into the SIP will remain applicable requirement until the revisions to 326 IAC 6-3 are approved into the SIP and the condition is modified in a subsequent permit action.

Pursuant to 40 CFR 52, Subpart P, the particulate emissions from the surface coating operation consisting of four (4) spray booths shall be limited by the following:

Interpolation of the data for the process weight rate up to sixty thousand (60,000) pounds per hour shall be accomplished by use of the equation:

$$E = 4.10 P^{0.67}$$
 where $E =$ rate of emission in pounds per hour and $P =$ process weight rate in tons per hour

Under the rule revision, particulate from the surface coating operation consisting of four (4) spray booths shall be controlled by dry filters, and the Permittee shall operate the control device in

Total Interior Systems - America, LLC 7 of 8
Princeton, Indiana F051-17729-00045

Permit Reviewer: ERG/SD

accordance with manufacturer's specifications.

State Rule Applicability - One (1) 1000 kW Emergency Generator

According to the EPA guidance dated September 6, 1995, an emergency generator means a generator which has the sole function of providing backup power when electric power from the local utility is interrupted, and which in no case shall exceed 500 hours of operation per year.

Testing Requirements

No stack test is required in this FESOP because compliance with the FESOP limits for HAPs emissions can be determined by evaluating MSDS and keeping records of the amount of HAPs applied.

Compliance Requirements

Permits issued under 326 IAC 2-8 are required to ensure that sources can demonstrate compliance with applicable state and federal rules on a more or less continuous basis. All state and federal rules contain compliance provisions, however, these provisions do not always fulfill the requirement for a more or less continuous demonstration. When this occurs IDEM, OAQ, in conjunction with the source, must develop specific conditions to satisfy 326 IAC 2-8-4. As a result, compliance requirements are divided into two sections: Compliance Determination Requirements and Compliance Monitoring Requirements.

Compliance Determination Requirements in Section D of the permit are those conditions that are found more or less directly within state and federal rules and the violation of which serves as grounds for enforcement action. If these conditions are not sufficient to demonstrate continuous compliance, they will be supplemented with Compliance Monitoring Requirements, also Section D of the permit. Unlike Compliance Determination Requirements, failure to meet Compliance Monitoring conditions would serve as a trigger for corrective actions and not grounds for enforcement action. However, a violation in relation to a compliance monitoring condition will arise through a source's failure to take the appropriate corrective actions within a specific time period.

The compliance monitoring requirements applicable to this source are as follows:

- 1. The surface coating operation consisting of four (4) spray booths have applicable compliance monitoring conditions as specified below:
 - (a) Daily inspections shall be performed to verify the placement, integrity and particle loading of the filters. To monitor the performance of the dry filters, weekly observations shall be made of the overspray from the surface coating booth stacks (01, 02, 03 and 04) while one or more of the booths are in operation. The Compliance Response Plan shall be followed whenever a condition exists which should result in a response step. Preparation, Implementation, Records, and Reports in accordance with Section C Compliance Response Plan Preparation, Implementation, Records, and Reports, shall be considered a violation of this permit.
 - (b) Monthly inspections shall be performed of the coating emissions from the stack and the presence of overspray on the rooftops and the nearby ground. The Compliance Response Plan for this unit shall contain troubleshooting contingency and response steps for when a noticeable change in overspray emission, or evidence of overspray emission is observed. The Compliance Response Plan shall be followed whenever a condition exists which should result in a response step.

Total Interior Systems - America, LLC 8 of 8
Princeton, Indiana F051-17729-00045

Permit Reviewer: ERG/SD

Failure to take response steps in accordance with Section C - Compliance Response Plan - Preparation, Implementation, Records, and Reports, shall be considered a violation of this permit.

(c) Additional inspections and preventive measures shall be performed as prescribed in the Preventive Maintenance Plan.

These monitoring conditions are necessary because the dry filers must function properly to ensure compliance with 326 IAC 6-3-2 (Process Operations) and 40 CFR 52, Subpart P.

Conclusion

The operation of this vehicle door panel manufacturing plant shall be subject to the conditions of the attached FESOP No. F051-17729-00045.

Appendix A: Emissions Calculations VOC and PM/PM10 From Surface Coating Operations

Company Name: Total Interior Systems - America, LLC

Address: RR 1 Box 101 County Road 100, Princeton, Indiana 47670

FESOP: 051-17729
PIt ID: 051-00045
Reviewer: ERG/SD
Date: July 10, 2003

Units	Material		Weight % Volatile (H20 & Organics)	Weight % Water	Weight % Organics	Volume % Water	Volume % Non- Volatiles (solids)	Max. Usage Rate (gal/hour)	Pounds VOC per gallon of coating less water	Pounds VOC per gallon of coating	PTE VOC (lb/hour)	PTE VOC (lb/day)	PTE VOC (tons/year)	PTE PM/PM10 (ton/year)	* Transfer Efficiency	PTE PM/PM10 (lb/hour)
EU01	Thinner	7.22	100%	0.0%	100.0%	0.0%	26.1%	0.12	7.22	7.22	0.88	21.1	3.86	0.00	65%	0.00
	Lacquer	5.32	73.9%	0.0%	73.9%	0.0%	26.1%	0.28	3.93	3.93	1.11	26.7	4.87	0.60	65%	0.14
EU02	Penguin Cement	0.86	78.0%	0.0%	78.0%	0.0%	12.0%	8.64	0.67	0.67	5.80	139	25.4	2.51	65%	0.57
EU03	Penguin Cement	0.86	78.0%	0.0%	78.0%	0.0%	12.0%	8.64	0.67	0.67	5.80	139	25.4	2.51	65%	0.57
EU04	Penguin Cement	0.86	78.0%	0.0%	78.0%	0.0%	12.0%	8.64	0.67	0.67	5.80	139	25.4	2.51	65%	0.57
	TOTAL SUM		·				•				19 38		84.9	8 12		

* Material applied with HVLP guns

METHODOLOGY

Pounds of VOC per gallon coating less Water = Density (lb/gal) * Weight % Organics * 1/ (1-Volume % Water)

Pounds of VOC per gallon coating = Density (lb/gal) * Weight % Organics

PTE VOC (lb/hour) = Pounds of VOC per Gallon coating (lb/gal) * Max. Throughput (gal/hour)

PTE VOC (lb/day) = Pounds of VOC per Gallon coating (lb/gal) * Max.Throughput (gal/hour) * 24 hour/day

PTE VOC (tons/year) = Pounds of VOC per Gallon coating (lb/gal) * Max. Throughput (gal/hour) * 8760 hours/year * 1 ton/2000 lbs

PTE PM/PM10 (tons/year) = Max. Throughput (gal/hour) * Density (lb/gal) * (1- Weight % Volatile) * (1-Transfer Efficiency) * 8760 hours/year * 1ton/2000 lbs

PTE PM/PM10 (lbs/hour) = Max. Throughput (gal/hour) * Density (lb/gal) * (1- Weight % Volatile) * (1-Transfer Efficiency)

Actual VOC (lbs/day) = PTE (lbs/hour) * 2080 hours/year * 1year/260 days of operation

Appendix A: Emissions Calculations HAP Emissions From Surface Coating Operations

Company Name: Total Interior Systems - America, LLC

Address: RR 1 Box 101 County Road 100, Princeton, Indiana 47670

FESOP: 051-17729
Plt ID: 051-00045
Reviewer: ERG/SD
Date: July 10, 2003

WEIGHT CONTENT IN PERCENT (%) OF HAPS

Material	Density	Max. Usage Rate	Weight %	Weight %	Weight %	Weight %	Weight %	Weight %	Weight %	Weight %
	(lb/gal)	(gal/hour)	Xylene	1-Butanol	Methyl Alcohol	Ethylbenzene	4-Methyl-2-Pentanone	Toluene	Hexane	Ethyl Acetate
Thinner	-	-	2.25%				5.0%	20.0%		
Lacquer	-	-	17.0%	0.98%	0.11%	3.20%	1.74%	38.7%		
Penguin Cement	Given	Below						15.0%	20.0%	40%
Penguin Cement	-	-						15.0%	20.0%	40%
Penguin Cement	-	-						15.0%	20.0%	40%

POTENTIAL TO EMIT OF HAPS

Material	Density	Max. Usage Rate	PTE Xylene	PTE 1-Butanol	PTE Methyl Alcohol	PTE Ethylbenzene	PTE 4-Methyl-2-Pentanone	PTE	PTE	PTE
	(lb/gal)	(gal/hour)	(ton/year)	(ton/year)	(tons/year)	(tons/year)	(tons/year)	Toluene	Hexane	Ethyl Acetate
Thinner	7.22	0.12	0.09	0.00	0.00	0.00	0.19	0.77	0.00	0.00
Lacquer	5.32	0.28	1.12	0.06	0.01	0.21	0.11	2.55	0.00	0.00
Penguin Cement	0.86	8.64	0.00	0.00	0.00	0.00	0.00	4.88	6.51	13.0
Penguin Cement	0.86	8.64	0.00	0.00	0.00	0.00	0.00	4.88	6.51	13.0
Penguin Cement	0.86	8.64	0.00	0.00	0.00	0.00	0.00	4.88	6.51	13.0
		TOTAL SUM =	1.21	0.06	0.01	0.21	0.31	18.0	19.5	39.1

HIGHEST SINGLE HAP (Ethyl Acetate) = 39.1 TOTAL HAPs = 78.3

METHODOLODY

Potential To Emit HAPs (tons/year) = Density (lb/gal) * Max. Usage Rate (gal/hour) * Weight % HAP * 8760 hours/year * 1 ton/2000 lbs

Appendix A: Emission Calculations One (1) Emergency Generator Using Fuel No. 2

Company Name: Total Interior Systems - America, LLC

Address: RR 1 Box 101 County Road 100, Princeton, Indiana 47670

FESOP: 051-17729
Plt ID: 051-00045
Reviewer: ERG/SD
Date: July 10, 2003

Heat Input Capacity

MMBtu/hour

Potential Throughput

kgals/year

1.5

3.41 11.85

Pollutant

Emission Factor (lb/kgal)	PM/PM10* 2.0	SO₂ 213 (142.0 S)	NO _x 20.0	VOC 0.34	CO 5.0
** Potential To Emit (tons/year)	0.012	1.262	0.119	0.002	0.030

^{*}PM emission factor is filterable PM only. Condensable PM emission factor is 1.3 lb/kgal. Assume all PM emissions are equal to PM10.

Note: Emission factors are from AP-42, Tables 1.3-1, 1.3-2, and 1.3-3 (SCC 1-03-005-01/02/03) Supplement E 9/98. 1 gallon of No. 2 Fuel Oil has a heating value of 144,000 Btu per gallon.

METHODOLOGY

Potential Throughput (kgals/year) = Heat Input Capacity (MMBtu/hour) * 500 hours/year * 1 kgal/1000 gal * 1 gal/0.144000 MMBtu Potential To Emit (tons/year) = Potential Throughput (MMCF/year) * Emission Factor (lb/kgal) * 1 ton//2000 lbs

See page 4 for HAPs emissions calculations.

^{**} According to EPA's guidance, an emergency generator is a unit operating less than 500 hours per year.

Appendix A: Emission Calculations One (1) Emergency Generator Using Fuel No.2

Company Name: Total Interior Systems - America, LLC

Address: RR 1 Box 101 County Road 100, Princeton, Indiana 47670

FESOP: 051-17229
Plt ID: 051-00045
Reviewer: ERG/SD
Date: July 10, 2003

HAPs - Metals

Emission Factor (lb/MMBtu)	Arsenic	Beryllium	Cadmium	Chromium	Lead
	4.0E-06	3.0E-06	3.0E-06	3.0E-06	9.0E-06
Potential To Emit (tons/year)	3.41E-06	2.56E-06	2.56E-06	2.56E-06	7.68E-06

HAPs - Metals (continued)

	i 3 Mictais (cont	macaj		
Emission Factor (lb/MMBtu)	Mercury 3.0E-06	Mangamese 6.0E-06	Nickel 3.0E-06	Selenium 1.5E-05
Potential To Emit (tons/year)	2.56E-06	5.12E-06	2.56E-06	1.28E-05

No data was available in AP-42 for organic HAPs.

METHODOLOGY

Potential To Emit (tons/year) = Heat Input Capacity (MMBtu/hr) * Emission Factor (lb/MMBtu) * 500 hours/year * 1 ton/2000lb

Appendix A: Emission Calculations Summary

Company Name: Total Interior Systems - America, LLC

Address: RR 1 Box 101 County Road 100, Princeton, Indiana 47670

FESOP: 051-17729
PIt ID: 051-00045
Reviewer: ERG/SD
Date: July 10, 2003

POTENTIAL TO EMIT BEFORE CONTROLS IN TONS PER YEAR

Emission Unit	PM	PM10	SO ₂	NOx	VOC	CO	Total HAPs	* Single Highest HAP
Surface Coating Operation								
EU 01	0.60	0.60			8.73			
EU 02	2.51	2.51			25.4		78.3	39.1
EU 03	2.51	2.51			25.4			
EU 04	2.51	2.51			25.4			
Emergency Generator	0.012	0.012	1.26	0.12	0.002	0.03		
TOTAL SUM	8.13	8.13	1.26	0.12	84.9	0.03	78.3	39.1

^{*} Ehthly Acetate